GAS-Mate®



SPECIFICATIONS	
Includes	GAS-Mate Combustible gas sensor Two D-size alkaline batteries Carrying case
Compatible gases and refrigerants	Propane (R290), isobutane (R600a), R441a, hydrogen forming gas (95/5), natural gas, methane, ammonia, and more
Sensitivity	5 ppm for methane, propane (R290), isobutane (R600a), and hydrogen 1 ppm for gasoline
Power source	Two D-size alkaline batteries (use Duracell® MN1300 to maintain intrinsically safe approval)
Battery life	25 hours
Weight	1.54 lb. (700 g)
Certifications	CE Intrinsically safe for Class I, Division I, Groups A - D, T4 and II 3G Ex nA nL IIC T4 X as per MET Laboratories Listing #E112145
Probe length	15 in. (38 cm)
Warranty	Three-year over-the-counter



ORDERING INFORMATION 718-202-G1 **Accessories and Replacement Parts** Sensor 706-700-G1 718-701-G1 Carrying case

ADVANTAGES

- Detects natural gas, propane, isobutane, ammonia, hydrogen forming gas (95/5), and more
- Ultimate sensitivity of 5 ppm for methane, R290 (propane), and R600a (isobutane)
- Intrinsically safe for use in combustive/ explosive environments
- Great for flammable refrigerants like R290, R600a, and R441a
- Runs on two D-cell batteries



■ WATCH OUR VIDEO!

