

Suit for
R32

VALUE
VALUE Creates Value

Making Your Job More Enjoyable

VRR24M-C

Recovery Unit



Double condenser

Light • Fast

DC brushless Motor

- Faster recovery
- Lighter

Oil-free Compressor

- Suitable for all commonly used refrigerants

Better Visibility

- Easy to read large LCD display
- Backlit display for clarity

Self-purge Function

- Prevent mixing of various refrigerants

Micro Channel Condenser

- Fast recovery
- Better cooling performance compare to traditional condenser

Model		VRR24M-C		
Refrigerant		Categories III : R12, R134a, R401C, R500, 1234yf Categories IV : R22, R401A, R401B, R402B, R407C, R407D, R408A,R409A,R411A R411B,R412A,R502,R509 Categories V : R402A,R404A,R407A,R407B,R410A,R507,R32		
Power Supply		220-240V~50/60Hz	115V~/60Hz	
Motor		Brushless DC motor 1HP		
Motor Speed		3000 rpm		
Maximal Current Draw		6.5 A	12 A	
Compressor		Oil-less, Air-cooled, Piston style		
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)		
Recovery Rate (kg/min)		Categories III	Categories IV	Categories V
	Vapor	0.43	0.54	0.54
	Liquid	3.60	4.00	4.20
	Push/Pull	7.50	8.50	9.50
Operating Temperature		0 °C-40 °C		
Dimensions		370×250×297 mm		
Weight		11 kg		