

VRDDF Recovery Unit

ATEX-Certified*

A1 A2L A2 A3

R290, R600a etc.

NEW



Sparkless
Power Supply



Oil-Free
Compressor



Brushless DC
Technology



ATEX-Certified

Safety · Reliability

Designed for R290, R600a

- Design reference to UL 121201, CSA C22.2 No. 213 and EN 60079-7 Standards

Fast and Efficient Recovery

- Brushless DC motor
- Twin cylinder with 2-row oversized condenser

Large Backlit Display

- Easy-to-read large LCD display
- Backlit for clarity

Oil-Free Compressor

- Suitable for all commonly used refrigerants

Purge Function

- Prevent mixing of various refrigerants

IP54 Design

- Tested to be waterproof and dustproof

Model		VRDDF		
Refrigerant		Categories III: R12, R134a, R401C, R500, 1234yf, R600a Categories IV: R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509, R290 Categories V : R402A, R404A, R407A, R407B, R410A, R507, R32, R507		
Power Supply		220-240V~50/60Hz	115V/60Hz	
Motor		Brushless DC motor 1HP		
Motor Speed		3000 rpm		
Maximal Current Draw		6.5 A	12 A	
Compressor		Oil-less, Air-cooled, Piston style		
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)		
Recovery Rate (kg/min)		Categories III	Categories IV	Categories V
	Vapor	0.43	0.54	0.54
	Liquid	3.60	4.00	4.20
	Push/Pull	7.50	8.50	9.50
Operating Temperature		0 °C-40 °C		
Dimensions		370×250×297 mm		
Weight		11 kg		

*ATEX No.: CSANe 22ATEX1032X